

LED HIGH BAY

CECHY:

Wysoka wydajność

Świetne odprowadzanie temperatury

Długotrwałość

Temperatura pracy: -30°C do 50°C



FSH701



FSH801

ZASTOSOWANIE

Magazyny, Fabryki, Hale, Parkingi, Lotniska i inne miejsca publiczne

Symbol	Moc[W]	CCT[K]	Lumeny[lm]	PF	Kąt[°]
FSH701 40W	40	3000/4000/6500	3500/3600/3800	0.9	60/90
FSH701 60W	60	3000/4000/6500	5250/5400/5700	0.9	60/90
FSH701 80W	80	3000/4000/6500	7000/7200/7600	0.9	60/90
FSH701 100W	100	3000/4000/6500	8750/9000/9500	0.9	60/90
FSH701 120W	120	3000/4000/6500	10500/10850/11400	0.9	60/90
FSH701 150W	150	3000/4000/6500	13100/13550/14250	0.9	60/90
FSH701 200W	200	3000/4000/6500	17500/18050/19000	0.9	60/90
FSH701 250W	250	3000/4000/6500	21850/22550/23750	0.9	60/90
FSH801 100W	100	3000/4000/6500	8750/9000/9500	0.9	60/90
FSH801 150W	150	3000/4000/6500	13100/13550/14250	0.9	60/90
FSH801 200W	200	3000/4000/6500	21850/22550/23750	0.9	60/90